MAC VENDING CART

Electric 3-Wheeler. Powered by Lithium-ion Technology

KAAM ZYADA DAAM KAM

- 7 121A, 121B Gurukul Indraprastha Industrial. Green Valley Faridabad, Haryana -121010
- sales@macauto.in
- Sales Support : 08090629062



MAC VENDING CART

KAAM ZYADA DAAM KAM

Better Payload Capacity

If the looks impress you, try and see its performance, with a high loading capacity and low maintenance, it has the potenioal of serving many tasks.

Smart Controlling System

Smart Control Systems can provide the most robust, versastile, custom made smart solutions of any type anywhere.

Driver Information System

Improve driving safety and efficiency by providing instructions to drivers aimed at improving their driving style.



LET'S E-START INDIA



Product Specification & features Mac Vending Cart Comfort Stylish Cushion Driver Seat ✓ Stylish Dumper & Front Panel ✓ Brighter Headlight ✓ Realistic Graphic ✓ Comfort Hittlon / Bonded High Relaxable Cushion seat Hittlon / Bonded Armrest X Rear Shock Absorber X Sacurity ✓ Hand Gripper ✓ Hand Gripper ✓ Hand Brake Sensor ✓ Front Brake Sensor ✓ Frash Shake Sensor ✓ Transmission Differential Differential Differential Battery Capacity Battery Capacity Battery Capacity Battery Capacity Battery Capacity Pattery in Series			
Stylish Cushion Driver Seat Stylish Bumper & Front Panel Brighter Headlight Reallstic Graphic Comfort High Relaxable Cushion seat Hitlon / Bonded Armrest X Armrest Rear Shock Absorber Sacurity Hand Gripper Hand Gripper Hand Brake Sensor Front Brake Sensor Transmission Wheel Drive Rear Wheel Drive Battery Connection Battery Connection 4 Battery in Series Performance Running Distance Purning Circle diameter Chassis Suspension Brake Dia Steering System Armest Ar	Product Specification & features	Mac Vending Cart	Mac Vending Cart+
Stylish Bumper & Front Panel ✓ ✓ Brighter Headlight ✓ ✓ Realistic Graphic ✓ ✓ Comfort Hitlon / Bonded Hitlon / Bonded High Relaxable Cushion seat Hitlon / Bonded Hitlon / Bonded Armest × ✓ Rear Shock Absorber × ✓ Sacurity ✓ ✓ Hand Gripper ✓ ✓ Handle Locking × ✓ Safety ✓ ✓ Front Brake Sensor ✓ ✓ Handle Rake System ✓ ✓ Rear Brake Sensor ✓ ✓ Transmission Differential Differential Gear Ration 10:01 10:01 Battery Capacity Battery Capacity Battery Connection 4 Battery in Series 4 Battery in Series Running Distance 90-100Km / Charge 90-100Km / Charge 10:01 10:01 Running Directe diameter 2.8m 2.8m 2.8m Chass	Comfort		
Brighter Headlight ✓ ✓ Realistic Graphic ✓ ✓ Comfort High Relaxable Cushion seat Hitton / Bonded Hitton / Bonded High Relaxable Cushion seat Hitton / Bonded Hitton / Bonded Armrest × ✓ Rear Shock Absorber × ✓ Security — ✓ Hand Gripper ✓ ✓ Hand Gripper ✓ ✓ Hand Gripper ✓ ✓ Hand Brake Sensor ✓ ✓ Front Brake Sensor ✓ ✓ Front Brake Sensor ✓ ✓ Transmission Differential Differential Gear Ration 10:01 10:01 Battery Capacity Battery Capacity Battery Capacity Battery Connection 4 Battery in Series 4 Battery in Series Performance Running Distance 90-100Km / Charge 90-100Km / Charge Turning Circle diameter 2.8m 2.8m Chassis Suspension	Stylish Cushion Driver Seat	✓	✓
Realistic Graphic	Stylish Bumper & Front Panel	✓	✓
Comfort	Brighter Headlight	✓	✓
High Relaxable Cushion seat Armrest X Rear Shock Absorber Security Hand Gripper Handle Locking X Safety Front Brake Sensor Wheel Drive Rear Brake Sensor Transmission Wheel Drive Battery Capacity Battery Capacity Rear Brake Sensor Leaf Spring & Rear Shocker Brake System Performance Running Distance Purplicate diameter Chassis Suspension Leaf Spring & Rear Shocker Brake System Leaf Spring & Rear Rods Front & Rear Rods F	Realistic Graphic	✓	✓
Armrest x ✓ Rear Shock Absorber x ✓ Security ✓ ✓ Hand Gripper ✓ ✓ Handle Locking x ✓ Safety ✓ ✓ Front Brake Sensor ✓ ✓ Hand Brake System ✓ ✓ Rear Brake Sensor ✓ ✓ Transmission Differential Differential Gear Ration 10:01 10:01 Battery Capacity Battery Connection 4 Battery in Series Performance 4 Battery in Series 4 Battery in Series Running Distance 90-100Km / Charge 90-100Km / Charge Turning Circle diameter 2.8m 2.8m Chassis Suspension Leaf Spring & Rear Shocker Leaf Spring & Rear Rods Front & Rear Rods Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm 130mm 130mm Rear Brake Dia 160mm Steering Handle Steering Handle Wheel / R	Comfort		
Rear Shock Absorber Security Hand Gripper Handle Locking Safety Front Brake Sensor Hand Brake System Rear Brake Sensor Wheel Drive Transmission Wheel Drive Rear Wheel Driver Rear Brake Sensor Differential Gear Ration Battery Capacity Battery Connection Handle Locking A Battery in Series Performance Running Distance Punning Circle diameter Chassis Suspension Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front	High Relaxable Cushion seat	Hitlon / Bonded	Hitlon / Bonded
Security Hand Gripper Hand Gripper Handle Locking Safety Front Brake Sensor Hand Brake System Rear Brake Sensor Wheel Drive Transmission Wheel Drive Rear Wheel Driver Rear Brake Sensor Transmission Differential Gear Ration Battery Capacity Battery Connection Handle Drive Rear Wheel Drive Battery Connection Handle Drive Rear Wheel Drive Battery Connection Handle Drive Battery Connection Handle Drive Battery Connection Leaf Spring & Rear Shocker Frontance Running Distance Dufferential Chassis Suspension Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front & Rea	Armrest	×	✓
Hand Gripper	Rear Shock Absorber	×	✓
Handle Locking Safety Front Brake Sensor Hand Brake System Rear Brake Sensor ✓ Transmission Wheel Drive Rear Wheel Driver Transmission Differential Gear Ration Battery Capacity Battery Connection Running Distance Running Distance Performance Running Circle diameter Chassis Suspension Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front &	Security		
Front Brake Sensor Hand Brake System Rear Brake Sensor Wheel Drive Transmission Wheel Drive Rear Wheel Driver Transmission Differential Gear Ration Battery Capacity Battery Connection Performance Running Distance 90-100Km / Charge Turning Circle diameter Chassis Suspension Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front Brake Dia Steering System Steering System Steering Handle Wheel / Rim Tyre Tube Type3.75x12" Weight Vehicle Kerb Weight A Wheel Jive V A Water Wheel Driver Rear Brake Dia Rear Brake Dia Rear Broke Rear Broke Steering Handle Wheel / Rim Tube Type3.75x12" Weight Vehicle Kerb Weight A Water Water Advance A Battery in Series 4 Battery in Series Fear Brake Sensor 10:01 10	Hand Gripper	✓	✓
Front Brake Sensor Hand Brake System Rear Brake Sensor Transmission Wheel Drive Rear Wheel Driver Rear Brake Sensor Transmission Differential Gear Ration Battery Capacity Battery Connection 4 Battery in Series 4 Battery in Series Performance Running Distance 90-100Km / Charge 7 Urning Circle diameter Chassis Suspension Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front Brake Dia 160mm Steering System Steering Handle Wheel / Rim 215x12"(MS RIM) Tyre Tube Type3.75x12" Weight Vehicle Kerb Weight 380kg 380kg	Handle Locking	×	✓
Hand Brake System Rear Brake Sensor Transmission Wheel Drive Rear Wheel Drive Rear Brake Sensor Transmission Differential Gear Ration Battery Capacity Battery Connection 4 Battery in Series 4 Battery in Series Performance Running Distance 90-100Km / Charge 90-100Km / Charge 7 Urning Circle diameter Chassis Suspension Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front & Rear Rods Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm Rear Brake Dia 160mm Steering System Steering Handle Wheel / Rim 215x12"(MS RIM) Tyre Tube Type3.75x12" Weight Vehicle Kerb Weight 380kg 380kg	Safety		
Rear Brake Sensor Transmission Wheel Drive Rear Wheel Driver Rear Brake Sensor Transmission Differential Differential Differential Gear Ration 10:01 Battery Capacity Battery Connection 4 Battery in Series 4 Battery in Series Performance Running Distance 90-100Km / Charge 90-100Km / Charge 12.8m 2.8m Chassis Suspension Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front &	Front Brake Sensor	✓	✓
Transmission Wheel Drive Rear Wheel Driver Rear Brake Sensor Transmission Differential Differential Gear Ration 10:01 10:01 Battery Capacity Battery Connection 4 Battery in Series 4 Battery in Series Performance Running Distance 90-100Km / Charge 90-100Km / Charge Turning Circle diameter 2.8m 2.8m Chassis Suspension Leaf Spring & Rear Shocker Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm 130mm Rear Brake Dia 160mm 160mm Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Tube Type3.75x12" Weight Vehicle Kerb Weight 380kg 380kg	Hand Brake System	✓	✓
Wheel DriveRear Wheel DriverRear Brake SensorTransmissionDifferentialDifferentialGear Ration10:0110:01Battery CapacityBattery Connection4 Battery in Series4 Battery in SeriesPerformancePerformance90-100Km / Charge90-100Km / ChargeRunning Distance90-100Km / Charge90-100Km / ChargeTurning Circle diameter2.8m2.8mChassis2.8m2.8mSuspensionLeaf Spring & Rear ShockerLeaf Spring & Rear ShockerBrake SystemFront & Rear RodsFront & Rear RodsFront Brake Dia130mm130mmSteering Brake Dia160mm160mmSteering SystemSteering HandleSteering HandleWeel / Rim215x12"(MS RIM)215x12"(MS RIM)TyreTube Type3.75x12"Tube Type3.75x12"WeightVehicle Kerb Weight380kg380kg	Rear Brake Sensor	✓	✓
Transmission Differential Differential Gear Ration 10:01 10:01 Battery Capacity Battery Connection 4 Battery in Series 4 Battery in Series Performance Running Distance 90-100Km / Charge 90-100Km / Charge Turning Circle diameter 2.8m 2.8m Chassis Suspension Leaf Spring & Rear Shocker Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm 130mm Rear Brake Dia 160mm 160mm Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Weight Vehicle Kerb Weight 380kg 380kg	Transmission		
Gear Ration 10:01 10:01 Battery Capacity 4 Battery in Series 4 Battery in Series Performance 90-100Km / Charge 90-100Km / Charge Running Distance 90-100Km / Charge 90-100Km / Charge Turning Circle diameter 2.8m 2.8m Chassis Leaf Spring & Rear Shocker Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm 130mm Rear Brake Dia 160mm 160mm Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Tube Type3.75x12" Weight 380kg 380kg	Wheel Drive	Rear Wheel Driver	Rear Brake Sensor
Battery Capacity Battery Connection 4 Battery in Series 4 Battery in Series Performance Running Distance 7 2.8m 1.8m 2.8m 2.8m Chassis Suspension Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm 130mm Rear Brake Dia 160mm Steering System Steering System Steering Handle Wheel / Rim 215x12"(MS RIM) Tyre Tube Type3.75x12" Weight Vehicle Kerb Weight 380kg 380kg	Transmission	Differential	Differential
Battery Connection 4 Battery in Series 4 Battery in Series Performance Running Distance 90-100Km / Charge 90-100Km / Charge Turning Circle diameter 2.8m 2.8m Chassis Suspension Leaf Spring & Rear Shocker Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm 130mm Rear Brake Dia 160mm 160mm Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Weight Vehicle Kerb Weight 380kg 380kg	Gear Ration	10:01	10:01
Performance 90-100Km / Charge 90-100Km / Charge Turning Circle diameter 2.8m 2.8m Chassis 2.8m 2.8m Suspension Leaf Spring & Rear Shocker Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm 130mm Rear Brake Dia 160mm 160mm Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Tube Type3.75x12" Weight 380kg 380kg	Battery Capacity		
Running Distance90-100Km / Charge90-100Km / ChargeTurning Circle diameter2.8m2.8mChassisSuspensionLeaf Spring & Rear ShockerLeaf Spring & Rear ShockerBrake SystemFront & Rear RodsFront & Rear RodsFront Brake Dia130mm130mmRear Brake DiaSteering HandleSteering HandleSteering SystemSteering HandleSteering HandleWheel / Rim215x12"(MS RIM)215x12"(MS RIM)TyreTube Type3.75x12"Tube Type3.75x12"WeightVelicle Kerb Weight380kg380kg	Battery Connection	4 Battery in Series	4 Battery in Series
Turning Circle diameter 2.8m 2.8m Chassis Suspension Leaf Spring & Rear Shocker Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm 130mm Rear Brake Dia 160mm 160mm Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Tube Type3.75x12" Weight 380kg 380kg	Performance		
Chassis Leaf Spring & Rear Shocker Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm 130mm Rear Brake Dia 160mm 160mm Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Tube Type3.75x12" Weight 380kg 380kg	Running Distance	90-100Km / Charge	90-100Km / Charge
Suspension Leaf Spring & Rear Shocker Leaf Spring & Rear Shocker Brake System Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm 130mm Rear Brake Dia 160mm 160mm Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Tube Type3.75x12" Weight 380kg 380kg	Turning Circle diameter	2.8m	2.8m
Brake System Front & Rear Rods Front & Rear Rods Front Brake Dia 130mm 130mm Rear Brake Dia 160mm 160mm Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Tube Type3.75x12" Weight 380kg 380kg	Chassis		
Front Brake Dia 130mm 130mm Rear Brake Dia 160mm 160mm Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Tube Type3.75x12" Weight 380kg 380kg	Suspension	Leaf Spring & Rear Shocker	Leaf Spring & Rear Shocker
Rear Brake Dia 160mm 160mm Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Tube Type3.75x12" Weight 380kg 380kg	Brake System	Front & Rear Rods	Front & Rear Rods
Steering System Steering Handle Steering Handle Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Tube Type3.75x12" Weight 380kg 380kg	Front Brake Dia	130mm	130mm
Wheel / Rim 215x12"(MS RIM) 215x12"(MS RIM) Tyre Tube Type3.75x12" Tube Type3.75x12" Weight 380kg 380kg	Rear Brake Dia	160mm	160mm
Tyre Tube Type3.75x12" Tube Type3.75x12" Weight 380kg 380kg	Steering System	Steering Handle	Steering Handle
Weight Vehicle Kerb Weight 380kg 380kg	Wheel / Rim	215x12"(MS RIM)	215x12"(MS RIM)
Vehicle Kerb Weight 380kg 380kg	Tyre	Tube Type3.75x12"	Tube Type3.75x12"
	Weight		
	Vehicle Kerb Weight	380kg	380kg
	Vehicle Gross Weight		800kg

Product Specification & features	Mac Vending Cart	Mac Vending Cart+
Outer Dimension		
Length	2760mm	2760mm
Width	940mm	940mm
Hight	1770mm	1770mm
Wheel Base	2125mm	2125mm
Ground Clearance form chassis	180mm	180mm
Loading Capacity		
Loading Capacity	up to 800 kgs	up to 800 kgs
Motor Details		
Motor Type	BLDC	BLDC
Motor Characteristic	48V1000W/32000RPM	48V1000W/32000RP
Water Ingress	IP 65	IP 65
Colling Type	Air Cool With fan	Air Cool With fan
Controller Details		
Controller Features	Overload protection	Overload protection
Reating	50 Amp	50 Amp
No. of Mosfets	24	24
Rating Volt	48V	
Water Ingress	IP65	IP65
Cooling Type	Heat Sink	Heat Sink
Controller Details		
Stepony Cover	Cloth	Cloth
Front Glass	×	✓
Central Locking	×	✓
Tool Kit	✓	✓
FM Radio	✓	✓
MP3	✓	✓
Rear Bumper	✓	✓
Fire Extinguisher	✓	✓
Brake Chargeable System	✓	✓
Front & Rear mud flap	✓	✓
Driver Foot Mat	×	×
Mobile Holder	×	✓
Front & Rear Light Mesh	√	✓